# 230\

# For sliding gates weighing up to 1500 kg.

Irreversible electromechanical gear motor.

## **Built-in control unit characteristics:**

- new control unit ROA37, with receiver compatible with encoding O-Code, Smilo, FloR and Flo. Reliable and safe: with electronic clutch and safety
- maximum protection of electronics against external disturbance with opto-isolated circuits.

anti-crushing protection

## Gear motor characteristics:

- easy and quick installation: external mounting, sturdy and practical plate
- sturdy and easy to use Nice die-cast aluminium key-operated unlock system
- prolonged lifetime and silent operations.

#### The kit contains:

#### TH1500

1 irreversible electromechanical gear motor, with incorporated control unit and plug-in receiver





**FLO2R-S**2 transmitters
433.92 MHz,
2 channels

Code	Description	Pc./pallet
TH1500KCE	Kit for the automation of sliding gates up to 1500 kg	16

N.B. The content of the package may vary: consult the retailer.

#### Technical specifications

reclinical specifications			
Code	TH1500		
Electrical data			
Power supply (Vac 50/60 Hz)	230		
Absorption (A)	1.6		
Power (W)	500		
Performance data			
Speed (m/s)	0.16		
Force (N)	800		
Work cycle (cycles/hour)	16		
Dimensional and general data			
Protection level (IP)	44		
Working temp. (°C Min/Max)	20 ÷ +50		
Dimensions (mm)	335x203x275 h		
Weight (kg)	13		

For updated and complete information, consult the product technical manual.