

AUTOMATIONS FOR **GARAGE & INDUSTRIAL DOORS**

supplied with control unit with integrated receiver



Pre-assembled belt drive for a faster installation, allows silent running



Fast and easy unlock device



Control panel and radio receiver included

Designed to comply with European safety standards.

versions available:

- **JM.3:** Operator with 600 N thrust, electronic control panel easy to adjust with trimmer and dip switches.
- **JM.4:** Operator with 1200 N thrust, electronic control panel with integrated programming display with easy interface system. Multiple operating logics and innovative thrust self learning system. Cycle counter

JIM

RESIDENTIAL USE BELT DRIVE

- 24 Vdc self-locking electromechanical operator for residential sectional garage doors
 - Encoder device for the detection of obstacles integrated in the control panel
 - Adjustable stroke by mechanical limits stop
 - Integrated courtesy light
- Operation continuity guaranteed in case of power failure with the battery back up unit integrable in the operator
 - Self-Learning limit switches

RAIL IS NOT INCLUDED
1 TO.GO2WV included





PTCL.3



Pre-assembled track with belt for doors up to H 2.5 m., internal, (for model JM.3 only), Single piece 3 m long

PTC.3



Pre-assembled track with belt for doors up to H 2.5 m. (for model JM.3 only), Two pieces 1,5 m each

PTC.4




Pre-assembled track with belt for doors up to H 2,5 m. (for model JM.4 only), Two pieces 1,5 m each

PTCL.4









Pre-assembled track with belt for doors up to H 3,5 m. (for model JM.3/JM.4 only), Two pieces 2 m each

AU.C25



Swaying arm for counterweight balanced doors



TECHNICAL DATA
JM.3
JM.4

Power supply	230 Vac	230 Vac
Motor supply	24 Vdc	24 Vdc
Absorbed Power	140 W	220 W
Max. absorbed current	1,0 A	1,5 A
Thrust	600 N	1200 N
Opening speed	13.1 m/1' - 9.8 m/1'	8.2 m/1' - 6.5 m/1'
Operation cycle	intensive use	intensive use
Protection level	IP 54	IP 54
Limit switch	electronic with encoder	electronic with encoder
Operating temp.	-20°C/+70°C	-20°C/+70°C
Rail	PTC.3	PTC.4
Receiver	built in	built in
Transmitter	1 TO.GO 2WW	1 TO.GO 2WW
Weight	5,9 Kg	7,6 Kg
Items no. per pallet	50	50

JM.SF


Wire unlock device

AU.MS60

 Handle for manual unlock.
 Door max thickness 50 mm

JM.PP

 Useful cord-type step by
 step comand which allows
 the automatic opening and
 closing of the door without any
 transmitter or push button

JM.CB

 Accessory for JM3/4 control
 panel composed of battery
 charger card and 1,2Ah batteries
 with support. This accessory
 allows the automatic use of the
 door even in case of power failure

**APPLE.2
 APPLE.4**

 433,92 Mhz rolling code
 transmitter, 2 or 4 channels. It with
 surface mounting holder
