



Belt

2-Year Full warranty
TÜV-tested to meet EN12453.
For doors up to 110 kg/13.5 m²

High quality accessories included in the carton



3-channel mini remote control



Wireless wall control

Input Voltage 230–240 V AC, 50 Hz
Max. Pull Force 800 N
Watts 125 W
Stand-by power 2.8 W

MOTOR

Type 24 V DC gearmotor permanent lubrication

DRIVE MECHANISM

Drive Belt with two-piece trolley on steel rail
Door height adjustable up to 2.3 m or up to 5 m with appropriate extension
Travel rate 127–178 mm per second
Lighting turns on when the drive is activated; turns off 2.5 minutes after closing
Door arm adjustable, trolley unlocking device

SAFETY

Automatic stop by pressing a button during forward or backward run and obstacle detection
Power recognition automatic
Overflow protection Transformer overload protection and low voltage cabling for accessories
Limit switch setting electronic, semi and fully automatic; optical detection of speed and door position

DIMENSIONS

Length (overall) 3.2 m
Headroom required 30 mm
Hanging weight 14.5 kg

RECEIVER

Memory Registers 12
Frequency 433.92 MHz

FURTHER FEATURES

Soft-start and soft-stop

SPECIAL NOTE

Chamberlain strongly recommends to install the protector system on all garage door openers!

NEW

In combination with the Multi-function control panel 78LM or 98LM the "PET & PED" function will be available for your convenience. With this function you can open your garage door as necessary – pet-function, pedestrian-function and automatic close.