

Dexxo Pro 1000 RTS



Dexxo Pro 1000 RTS

Automation of up & over, sectional, side hinged and lateral doors.

Product benefits

- Suitable for the automation of:
 - Door surfaces up to 15 m².
 - Up & over doors with a max. height of 3.15 m.
 - Sectional doors with a max. height of 3 m.
- Simple wiring of accessories with removable terminal block.
- Integrated lighting.
- Connection and independent control of external lighting is possible.
- High quality performance: up to 90,000 cycles.
- 5 year warranty on the motor and rail
- Compatible with RTS control range.
- Simple to install.
- The system can be commissioned in 90 seconds.
- Easy to set parameters via a display.
- Built in obstacle detection whereby the motor complies 100% to the European standard.
- The sensitivity of the obstacle detection can be adjusted.
- Partial opening (ventilation position) can be set.
- Soft stop and start.
- Belt and chain rails available.

Dexxo Pro 1000 RTS

	Reference number
Dexxo Pro 1000 RTS	1 216 169
2.9M single chain rail	9 013 811
2.9M 2 part chain rail	9 013 812
3.5M single chain rail	9 013 813
3.5M 2 part chain rail	9 013 814
2.9M single belt rail	9 013 815
2.9M 2 part belt rail	9 013 816
3.5M single belt rail	9 013 817
3.5M 2 part belt rail	9 013 818
2.9M high cycle chain rail	9 013 819
3.5M high cycle chain rail	9 013 820

Technical data

Main technical data:

Supply voltage:	230 V
Motor voltage:	24 V
Max. consumption in use:	350 W
Tensile strength:	1000 N
Max. surface area of the door:	15 m ²
External length	
- Rail 2.90 m:	3.24 m
- Rail 3.50 m:	3.74 m
Rail height:	3.2 cm
Number of programmable remote controls:	32
Max. number of cycles:	
- Standard rails	20 cycles/ day
- High cycle rail	50 cycles/ day
Remote control frequency:	433.42 Mhz
Operating temperature:	-20°C/ +60°C
Weight of the motor:	6.98 kg
Light (supplied)	
- Voltage:	230 V
- Capacity:	40 W
- Lamp	E 14
Maximum load of the external lighting:	230 V/ 500 W, Class II
Speed on opening:	18 cm/ s max.
Warranty:	5 years

Dexxo Pro Pack comprises:

- 1 Motor with integrated light and receiver.
- 2 Transmitters.
- 1 40W light.
- 1 Door support and 1 lintel support.
- 1 Connecting arm.
- Attachment hooks for the motor.
- 1 Bag with screws and installation parts.

Access >> Motors for garage doors

(189)

somfy®