

# Radio remote controls FM 868.8 MHz (Somlog Rollingcode)



## 4-command transmitter "Classic" 4020V000

- range: approx. 50 m (depending on surrounding)
- housing type stainless steel, body can be pulled out
- keypad cover prevents unintentional activity
- battery: 3 V, type CR 2032
- dimensions: 87 × 24 × 16 mm (when closed)



## Holder 4640V000

- for 4-command transmitter "Classic" (#4020V000)
- for fixing in a car or on a wall
- incl. fixing material



## Set with 4-command transmitter + holder 4650V000

- comprising: 4-command transmitter "Classic" (#4020V000) and holder (#4640V000), incl. fixing material



## 4-command transmitter "Slider" 4031V000

- range: approx. 35 m (depending on surrounding)
- housing with slider function
- high-quality, modern design in stainless steel application
- battery: 3 V, type CR 2032
- dimensions: 62 × 35 × 16 mm (when closed)



## 2-command transmitter "Ruby" 4035V002

- range: approx. 25 m (depending on surrounding)
- battery: 3 V, type CR 2032
- dimensions: 81 × 24 × 12 mm



## Holder 4642V000

- for 2-command transmitter "Ruby" (#4035V002)
- for fixing in a car or on a wall
- incl. fixing material



## 2-command transmitter "Mini" 4026V000

- range: approx. 50 m (depending on surrounding)
- battery: 3 V, type CR 2032
- dimensions: 88 × 24 × 13 mm



## 12-command transmitter "Telecodey" 4071V000

- can also be used as wireless keypad
- with illuminated buttons
- memory: 10 different access codes and 2 uncoded keys, e.g. for light
- range: approx. 25 m (depending on surrounding)
- battery: 3 V, type CR 123 A
- dimensions: 147 × 48 × 30 mm
- temperature range: -20°C bis +55°C
- weather-resistant; for internal and external installations
- incl. aluminium wall holder and fixing material

IP 64